

高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.

Solid Ink Coding Continuous Band Sealer

Solid-Ink Coding Continuous Band Sealer designed equipped with Solid-ink coding device is adopted to print the colored label on bag while sealing. Continuous Band Sealer with a conveyor that is much faster than a bar sealer, as the operator does not have to wait for the seal cycle to finish. Band sealers with conveyors is common using in production where fast, secure, hand-fed sealing is desired. Continuous Band Sealer save time, save money and improve efficiency.

Solid-Ink Coding Continuous Band Sealer are sealing machines designed to work for most plastic films made from various materials. Continuous Band Sealers are capable of sealing a wide range of bags such as stand-up pouches, gusseted bags, pillow-type bags, sachets, barriers bags, etc.

Solid-Ink Coding Continuous Band Sealer are typically used for low-to-medium-volume packaging, is used in the fields of domestic electrical appliance, foodstuffs, general merchandise, medicine and chemical industries.

FRM1120W Solid Ink Coding Continuous Band Sealer

FRM1120W Solid-Ink Coding Continuous Band Sealer design with Solid-ink coding device for printing expired date or code. Machine equipped with heavy duty conveyor motor able to load up to 2.5 Kgs packing (overall packing 7.5 Kgs).

FRM1120W Solid-Ink Coding Continuous Band Sealer equipped with digital temperature controllers and powder coated metal structure. Machine console with roller, flexible to move for difference packing area. Equipped solid-ink coding device adopted able to print the colored label on bag while sealing. Printing font size selectable for two lines in font size two (18PT) or three lines in font size five (10.5PT).

Optional: a. Stainless Steel Structure



Related Products:

Solid Ink Rolls are compatible with various hot ink coding printers and continuous band sealers that include hot roll printing coder. Hot ink rolls are foam rolls with hot melt inks, difference size and color options are available. Each hot roll can make approximately 90,000 prints, though this

Available Sizes: 32mmD x 16mmW

Available Color: Black & White





TECHNICAL DATA

Model	FRM1120W
Voltage	AC 240/50
Motor Power	100 W
Sealing Power	300 W x 2
Printing Heating Power	40 W x 2
Sealing Speed	0-12 M/min
Sealing Width	10 mm
Temperature Range (Digital)	0-300 (°C)
Printing Type	Solid Ink Roller
Distance from Sealing Centre to Conveyor Table	20 - 80 mm
Conveyor Table Size	1100mmL x 205mmW
Max. Conveyor Loading for Single Package	< 2.5 Kg
Overall Conveyor Loading	< 7.5 Kg
Machine Structure	Powder Coated
Machine Dimensions	1100mmL x 610mmW x 1030mm
Machine Weight	85 Kg