



高雄貿易有限公司

KAOH SIUNG TRADING SDN. BHD.



Shrink Packaging Machine

Shrink Packaging Machine also known as Heat tunnels are designed to blow hot air onto film wrapped packages to make perfect shrink around packages. The heat settings and conveyor speed of the shrink tunnel can be adjusted to properly heat a shrink film. The heat applied to the shrink film enables the film to tightly conform to the product within the film. Shrink tunnels are equipped with difference type of conveyor eg. roller conveyor, Teflon net conveyor or Stainless Steel Mesh to deliver difference size of product through shrink tunnel.

Shrink tunnels can be combined with the Sleeve Sealer, L-Sealer machines or overwrapping machines for the ultimate wrapping solution.

Shrink Packaging Machine is widely used in industries such as foodstuff, beverage, pharmacy, cosmetics and pesticide for containers with labels like glass bottle, plastic bottle, paper cup etc.

CN-E Series PE Shrink Packaging Machine - Digital Temperature Control

CN-E Series Shrink Packaging Machine suitable all kind of shrinkable films especially PE Shrink Film. PE Shrink tunnel designed for production to pack heavy products or outer packing protection. CN-E Series Shrink tunnel equipped with heavy duty conveyor motor able to load heavy products.

CN-E Series Shrink Packaging Machines a fully re-circulating air chamber and Cooling fans on discharge end of tunnel. CN-E Series Shrink Packaging Machine equipped with desired modern specifications of digital temperature control, adjustable conveyor speed. CN-E Series Heat Tunnel are built using the 1/4 HP blower motors, dead roller conveyor system, heating circulating type, silicon fiber tube on the conveyor rods.

CN-E Series Shrink Packaging Machine are long lasting machineries built with selected high quality electronic components and therefore will require lesser maintenance.

Optional: a. Stainless Steel Structure b. Customized specifications are available.



TECHNICAL DATA

Model	CN4530E	CN6530E	CN8540E
Voltage	3 Phase 415V	3 Phase 415V	3 Phase 415V
Max. Power	18000W	24000W	36000W
Shrinking Film Material	PE / PVC / POF / PP	PE / PVC / POF / PP	PE / PVC / POF / PP
Tunnel Dimension	1500mmL x 450mmW x 300mmH	1800mmL x 650mmW x 300mmH	2000mmL x 850mmW x 400mmH
Overall Conveyor Loading Weight	30 Kg	50 Kg	60 Kg
Conveyor Type	Roller / Teflon Mesh / Stainless Steel Mesh		
Conveyor Speed	2 - 8 M/min	2 - 8 M/min	2 - 8 M/min
Conveyor Dimension	2400mmL x 450mmW	3000mmL x 650mmW	3000mmL x 850mmW
Working Table Height	760mmH	760mmH	760mmH
Machine Structure	Metal with Powder Coated	Metal with Powder Coated	Metal with Powder Coated
Machine Weight	250 Kg	400 Kg	500 Kg
Machine Dimension	2400mmL x 790mmW x 1300mmH	3000mmL x 970mmW x 1400mmH	3000mmL x 1170mmW x 1500mmH