



# 高雄贸易有限公司

## KAOH SIUNG TRADING SDN. BHD.



### *Shrink Packaging Machine*

Shrink Packaging Machine also known as Heat tunnels are designed to blow hot air onto film wrapped packages to make perfect shrink around packages. The heat settings and conveyor speed of the shrink tunnel can be adjusted to properly heat a shrink film. The heat applied to the shrink film enables the film to tightly conform to the product within the film. Shrink tunnels are equipped with difference type of conveyor e.g. roller conveyor, Teflon net conveyor or Stainless Steel Mesh to deliver difference size of product through shrink tunnel.

Shrink tunnels can be combined with the Sleeve Sealer, L-Sealer machines or overwrapping machines for the ultimate wrapping solution.

Shrink Packaging Machine is widely used in industries such as foodstuff, beverage, pharmacy, cosmetics and pesticide for containers with labels like glass bottle, plastic bottle, paper cup etc.

### *CN-POF Series Shrink Packaging Machine - Digital Temperature Control*

CN-POF Series Shrink Packaging Machine designed for those packages that are larger or wider. CN-A Series Shrink Tunnels is suitable for PVC and POF shrinkable film.

CN-POF Series Shrink Packaging Machine equipped with desired modern specifications of digital temperature control for fully recirculating air chamber, adjustable conveyor speed.

CN-POF Series Shrink Packaging Machine are long lasting machineries built with selected high quality electronic components and therefore will require lesser maintenance.

*Optional: a. Stainless Steel Structure b. Customized specifications are available.*



#### TECHNICAL DATA

| Model                           | CN4520POF                     | CN6530POF                     | CN8540POF                     |
|---------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Voltage                         | 3 Phase 415V                  | 3 Phase 415V                  | 3 Phase 415V                  |
| Max. Power                      | 12000W                        | 15000W                        | 18000W                        |
| Shrinking Film Material         | PVC / POF / PP                | PVC / POF / PP                | PVC / POF / PP                |
| Tunnel Dimension                | 1200mmL x 450mmW x 200mmH     | 1200mmL x 650mmW x 300mmH     | 1200mmL x 850mmW x 400mmH     |
| Overall Conveyor Loading Weight | 20 Kg                         | 30 Kg                         | 30 Kg                         |
| Conveyor Type                   | Roller / Stainless Steel Mesh | Roller / Stainless Steel Mesh | Roller / Stainless Steel Mesh |
| Conveyor Speed                  | 2 - 8 M/min                   | 2 - 8 M/min                   | 2 - 8 M/min                   |
| Conveyor Dimension              | 2000mmL x 450mmW              | 2000mmL x 650mmW              | 2000mmL x 850mmW              |
| Working Table Height            | 760mmH                        | 760mmH                        | 760mmH                        |
| Machine Structure               | Metal with Powder Coated      | Metal with Powder Coated      | Metal with Powder Coated      |
| Machine Weight                  | 150 Kg                        | 260 Kg                        | 300 Kg                        |
| Machine Dimension               | 2000mmL x 730mmW x 1300mmH    | 2000mmL x 930mmW x 1400mmH    | 2000mmL x 1170mmW x 1500mmH   |