



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



## *KST Series Pneumatic Impulse Sealer*

KST Pneumatic Impulse Sealer is custom crafted from lightweight aluminium and designed for oversized and heavy duty packaging applications. KST Pneumatic Series are recommended for a variety of thermoplastic materials with multiple layers films, extra thickness and laminates.

## *KST Series Vertical Pneumatic Impulse Sealer with Suction System and Gas Flush*

KST Pneumatic Impulse Sealer design with heavy duty structural frame provides the structure stability necessary to make seals for a big size bag. KST Pneumatic Sealer is suitable for sealing various plastic film bags and AL-plastic compound bag with double heating sealer. It adopts compressed air as motive power with adjustable sealing pressure and reliable sealing quality, and its sealing operation can be controlled by manual.

KST Pneumatic Impulse Sealer controlled by electronic timers, once correct setting have been programmed, consistent seals and cooling are maintained automatically for perfect sealing quality.

KST Pneumatic Impulse Sealer are long lasting machineries built with selected high quality electronic components and therefore will require lesser maintenance.

*Optional: a. Customized specifications are available.*



### TECHNICAL DATA

MODEL	KST-A1000PV-SG	KST-A1000PV-S
Voltage (V)	1 Phase 240V	
Sealing Power (Depend Size and Number of Element)	1000W / 2000W	
Sealing Length	1000mm	
Sealing Width	3mm / 6mm / 10 mm	
Sealing Thickness	2 x 0.15mm / 0.4mm	
Suction Time	0 - 99 sec	
Gas Flush Time	0 - 99 sec	N/A
Air Compressor (prepare by customer)	0.4 - 0.6 Mpa	
Machine Structure	Aluminium Profile and Metal with Powder Coated	
Sealing Bar	Top & Bottom / Bottom Only	
Air Compressor (prepare by customer)	0.4 - 0.6 Mpa	
Machine Dimension	1690mmL X 1160mmW X 1870mmH	
Machine Weight	250 kg	