

## Bi-Active Semi Auto Impulse Sealers With Temperature Control

Heavy duty, single or double, automatic or manual impulse heat sealer. Seals up to 20mil gusseted or regular thermoplastic film. Separate programmable timers for material thickness, congealing, and operating cycle. Create perfect seals every time. Foot switch included for manual operation.

### TECHNICAL DATA

MODEL	ME-455FSA	ME-605FSA
Special Features	Digital Temperature Setting Control	
Voltage	AC 220V-240V	
Total Power	1900W	2300W
Sealing Length	450mm	600mm
Sealing Width	5mm	
Sealing Jaw	Double Jaw	
Heat Temperature	80 - 250°C	
Machine Dimension (L x D x H)	520 x 520 x 400 (mm)	670 x 520 x 400 (mm)
Machine Weight	22Kg	23Kg

### FSA SERIES



## Bi-Active Semi Auto Impulse Sealers with Motor and Temperature Control

Heavy duty, single or double, automatic or manual impulse heat sealer. Seals up to 20mil gusseted or regular thermoplastic film. The sealing pressure is over 0.7kg/cm<sup>2</sup> and comply with ISO operation standard. Separate programmable timers for material thickness, congealing, and operating cycle. Create perfect seals every time. Foot switch included for manual operation.

### FDE SERIES TECHNICAL DATA



MODEL	ME-455FDE	ME-605FDE
Special Features	Motor Pressure Control and Digital Temperature Setting	
Voltage	AC 220V-240V	
Total Power	1900W	2300W
Sealing Length	450mm	600mm
Sealing Width	5mm	
Sealing Jaw	Double Jaw	
Heat Temperature	80 - 250°C	
Machine Dimension (L x D x H)	520 x 520 x 400 (mm)	670 x 520 x 400 (mm)
Machine Weight	29Kg	30Kg

## Constant Heat Foot Sealer

Constant Heat Foot Sealers are excellent for sealing polycello films, humidity-proof cellophane film, polyethylene film, aluminium foil coated bags and gusset bags. We offer mesh or straight-line texture of heater jaw. The straight-line texture is especially recommend for health care industry. Each machine has new injection moulded castings and electro static paint. Machine equipped with protection mask for safety purpose. CFV sealer vertical sealing design to prevent stuff from overflow for packaging stuff like powder, liquid. Separate programmable timers for material thickness, sealing, and operating cycle. Foot switch included for manual operation mode. Equipped with mask preventing scald.

### TECHNICAL DATA

MODEL	ME-400CFN	ME-600CFV
Voltage	AC 220V-240V	
Total Power	420W	640W
Sealing Length	400mm	600mm
Sealing Width	10mm / 15mm	
Sealing Jaw	Double Jaw	
Heat Temperature	80 - 250°C	
Machine Dimension (L x D x H)	470 x 520 x 1000 (mm)	660 x 400 x 1400 (mm)
Machine Weight	23Kg	35Kg

### CF SERIES



高雄貿易有限公司

KAOH SIUNG TRADING SDN. BHD.

10, Jalan Rajawali 3, Bandar Puchong Jaya, 47100 Puchong, Selangor, Malaysia.



177229-T

**Tel: +603-80757011/2/3/4**

**Fax: +603-80757015**

**E-mail: [sales@kaohsiung.com.my](mailto:sales@kaohsiung.com.my) / [sales@kst.com.my](mailto:sales@kst.com.my)**

**Web: [www.kaohsiung.com.my](http://www.kaohsiung.com.my)**