



# 高雄貿易有限公司

## KAOH SIUNG TRADING SDN. BHD.



### Continuous Band Sealer

Continuous Band Sealer designed for light-duty continuous bag sealing applications. Continuous Band Sealer with a conveyor that is much faster than a bar sealer, as the operator does not have to wait for the seal cycle to finish. Band sealers with conveyors is common using in production where fast, secure, hand-fed sealing is desired. Continuous Band Sealer save time, save money and improve efficiency.

Continuous Band Sealer are sealing machines designed to work for most plastic films made from various materials. Continuous Band Sealers are capable of sealing a wide range of bags such as stand-up pouches, gusseted bags, pillow-type bags, sachets, barriers bags, etc.

Continuous Band Sealer sealers are typically used for low-to-medium-volume packaging, is used in the fields of domestic electrical appliance, foodstuffs, general merchandise, medicine and chemical industries.

### FR880 Series Automatic Continuous Band Sealer

FR880A Series Automatic Continuous Band Sealer is light-duty continuous bag sealing applications conveyor motor able to load up to 1 Kgs packing (overall packing 3Kgs). All of these machines using Stainless Steel housing and digital temperature controllers.

Three models available for difference packing requirement: FR880AI - Table top horizontal design for most of product; FR880AII - Table top vertical design for packing powder or liquid texture product; FR880AIII - Console with roller, flexible to move for difference packing area.

Optional: a. Gas Filling System



FR880AI



FR880AII



FR880AIII

#### TECHNICAL DATA

Model	FR880AI	FR880AII	FR880AIII
Voltage	1 Phase 240V	1 Phase 240V	1 Phase 240V
Motor Power / Sealing Power	50W / 300W x 2	50W / 300W x 2	50W / 300W x 2
Sealing Speed	0 - 8 M/min	0 - 8 M/min	0 - 8 M/min
Sealing Width	12 mm	12 mm	12 mm
Temperature Range (Digital)	0 - 300°C	0 - 300°C	0 - 300°C
Distance from Sealing Centre to Conveyor Table	0 - 40 mm	150 - 270 mm	10 - 40 mm
Conveyor Table Size	840mmL x 153mmW	840mmL x 153mmW	840mmL x 153mmW
Max. Conveyor Loading for Single Package	< 1 Kg	< 1 Kg	< 1 Kg
Overall Conveyor Loading	< 3 Kg	< 3 Kg	< 3 Kg
Machine Housing	Stainless Steel	Stainless Steel	Stainless Steel
Machine Dimension	840mmL x 380mmW x 320mmH	840mmL x 380mmW x 550mmH	840mmL x 550mmW x 800mmH
Machine Weight	32 Kg	37 Kg	40 Kg