



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



Continuous Band Sealer

Continuous Band Sealer designed for light-duty continuous bag sealing applications. Continuous Band Sealer with a conveyor that is much faster than a bar sealer, as the operator does not have to wait for the seal cycle to finish. Band sealers with conveyors is common using in production where fast, secure, hand-fed sealing is desired. Continuous Band Sealer save time, save money and improve efficiency.

Continuous Band Sealer are sealing machines designed to work for most plastic films made from various materials. Continuous Band Sealers are capable of sealing a wide range of bags such as stand-up pouches, gusseted bags, pillow-type bags, sachets, barriers bags, etc.

Continuous Band Sealer sealers are typically used for low-to-medium-volume packaging, is used in the fields of domestic electrical appliance, foodstuffs, general merchandise, medicine and chemical industries.

FRP Continuous Band Sealer with Thermal Inkjet Printer

FRP880A Series Thermal Inkjet Printer Continuous Band Sealer equipped with Thermal Inkjet coding device for printing expired date or code. Machine conveyor motor able to load up to 1 Kgs packing (overall packing 3 Kgs). All of these machines structure using Stainless Steel and digital temperature controllers. The Thermal Inkjet printer can print single or multiple-line prints up to, and within, the maximum print-height of 12.7mm.

Two models available for difference packing requirement: FRP880AI Table top horizontal design for most of product; FRBM880AIII Console with roller, flexible to move for difference packing area.

TECHNICAL DATA

Model	FRP880A I
Voltage	AC 220/50
Motor Power	245 W
Sealing Power	300 W x 2
Sealing Speed	0-16M/min
Sealing Width	10 mm
Temperature Range (Digital)	0-300 (°C)
Distance from Sealing Centre to Conveyor Table	20 - 40 mm
Conveyor Table Size	1400mmL x 250mmW
Max. Conveyor Loading for Single Package	< 1Kg
Overall Conveyor Loading	< 3 Kg
Machine Housing	Stainless Steel
Machine Dimensions	844mmL x 375mmW x 425mmH
Machine Weight	25Kg

Inkjet Printer Parameter

Printable Height	12.7mmH (No line limitation within the printing range)
Control Panel	5 inch Touch Screen
Printing Object	Text, Counter, Date/Time (Autorun), Logo, Shift Code, Barcode, QR Code
External Interface	USB interface, RS232 Serial Terminal



Related Products:

Solvent Based Inks are high-resolution printing for non-porous substrates. Solvent Based Inks are suitable to print on metal, plastic, foil. Multiple Colours Available: Black, Yellow, Red, Blue, White. (Ink Volume: 42ml)

Water Based Inks is range of general purpose inks suited for porous substrates. Water Based Inks are suitable to print on cardboard, paper, carton boxes, wood, chipboard. Multiple Colours Available: Black, Yellow, Red, Blue, Green. (Ink Volume: 42ml)

