V03.19 Company No. 177229-T



# 高雄贸易有限公司



# KAOH SIUNG TRADING SDN. BHD.

### Shrink Packaging Machine

Shrink Packaging Machine also known as Heat tunnels are designed to blow hot air onto film wrapped packages to make perfect shrink around packages. The heat settings and conveyor speed of the shrink tunnel can be adjusted to properly heat a shrink film. The heat applied to the shrink film enables the film to tightly conform to the product within the film. Shrink tunnels are equipped with difference type of conveyor eg. roller conveyor, Teflon net conveyor or Stainless Steel Mesh to deliver diffrence size of product through shrink tunnel.

Shrink tunnels can be combined with the Sleeve Sealer, L-Sealer machines or overwrapping machines for the ultimate wrapping solution.

Shrink Packaging Machine is widely used in industries such as foodstuff, beverage, pharmacy, cosmetics and pesticide for containers with labels like glass bottle, plastic bottle, paper cup etc.

### CN-A Series Mini Shrink Packaging Machine - Voltage Regulator

CN-A Series Mini Shrink Packaging Machine designed with fully recirculating air chamber. CN-A Series shrink tunnels is suitable for PVC film.

CN-A Series Shrink Packaging Machine equipped with voltage regulator for temperature control and adjustable conveyor speed.

CN-A Series Shrink Packaging Machine are long lasting machineries built with selected high quality electronic components and therefore will require lesser maintenance.

Optional: a. Stainless Steel Structure b. Customized specifications are available.



#### TECHNICAL DATA

Model	CN4015A	CN4520A	CN4520AL
Voltage	1 Phase 240	1 Phase 240 / 3 Phase 415V	1 Phase 240 / 3 Phase 415V
Max. Power	5000W	6000W	9600W
Shrinking Film Material	PVC	PVC	PVC / POF / PP
Tunnel Dimension	700mmL x 400mmW x 150mmH	800mmL x 450mmW x 200mmH	1000mmL x 450mmW x 200mmH
Overall Conveyor Loading Weight	10 Kg	20 Kg	20 Kg
Conveyor Type	Roller / Stainless Steel Mesh	Roller / Stainless Steel Mesh	Roller / Stainless Steel Mesh
Conveyor Speed	2 - 7 M/min	2 - 7 M/min	2 - 7 M/min
Conveyor Dimension	1050mmL x 400mmW	1200mmL x 450mmW	1500mmL x 450mmW
Working Table Height	690mmH	690mmH	785mmH
Machine Structure	Metal with Powder Coated	Metal with Powder Coated	Metal with Powder Coated
Machine Weight	90 Kg	110 Kg	120Kg
Machine Dimension	1180mmL x 620mmW x 1050mmH	1330mmL x 720mmW x 1100mmH	1650mmL x 720mmW x 1220mmH