V09.22 Company No. 177229-T



## 高雄贸易有限公司



## KAOH SIUNG TRADING SDN. BHD.

## Semi Automatic Double Heat Impulse Sealer

Semi Automatic Double Heat Impulse Sealers designed with two heating jaw (top and bottom) able to seal up to 18mil gusseted or regular thermoplastic film. Semi Automatic Double Impulse Sealers is best for all sealing purposes and recommended for a variety of other common thermoplastic materials including: Polyethylene, Polyurethane, Polyvinylchloride, Polyvinyl Alcohol, Nylon, bubble packs, padded mailers, foil, coated bags and etc.

Semi Automatic Double Heat Impulse Sealers are easy to use (no warm-up time), economical (electricity is only used when the jaw is lowered during the sealing process), and safe (no component of these devices is always hot) which is ideal for sealing operations in packaging candies, food, stationery, drugs, tools, replacement parts and a variety of other products.

## FDA Series Semi Automatic Impulse Sealer

FDA Series Semi Automatic Impulse Sealers is table top heavy duty sealing machine. FDA Series Semi Automatic Impulse Sealers designed with two heating jaw (top and bottom) able to seal up to 18mil gusseted or regular thermoplastic film. Two difference sealing length is available: 450mm and 600mm with 5mm or 10mm sealing width.

FDA Series Semi Automatic Double Impulse Sealers design with selectable single or double jaw heating, separate programmable timers for heating, congealing and recycling for different material thickness. FDA Series is easy operate and no operator training is required. Once correct setting have been programmed, consistent seals and cooling are maintained automatically for perfect sealing quality. Foot switch included for manual operation.



| TECHNICAL DATA       |                           |                           |
|----------------------|---------------------------|---------------------------|
| MODEL                | 455FDA / 4510FDA          | 605FDA / 6010FDA          |
| Voltage              | 1 Phase 240V              | 1 Phase 240V              |
| Sealing Power        | 2000W / 2500W             | 2500W / 2900W             |
| Sealing Length       | 450 mm                    | 600 mm                    |
| Sealing Width        | 5 mm / 10mm               | 5 mm / 10mm               |
| Sealing Jaw          | Top & Bottom              | Top & Bottom              |
| Heat Time Setting    | 0 - 2 sec                 | 0 - 2 sec                 |
| Cooling Time Setting | 0 - 4 sec                 | 0 - 4 sec                 |
| Machine Structure    | Die-Cast with powder coat | Die-Cast with powder coat |
| Machine Dimension    | 520mmL x 520mmD x 400mmH  | 660mmL x 520mmD x 400mmH  |
| Machine Weight       | 23Kg                      | 25Kg                      |