



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



Semi Automatic Impulse Sealer

Semi Automatic Pneumatic Impulse Sealer adopts with pneumatic cylinder required compressed air as motive power with adjustable sealing pressure and double heating sealer for reliable sealing quality.

Semi Automatic Pneumatic Impulse Sealer commonly used in the fields of animal feed, chemicals, aggregates, food, fertilizer, detergents, pet food, spices, sugar, grains and cereals, insulation, pellets, powders, etc.

SCP-W Series Semi Automatic Pneumatic Impulse Sealer with Water Cooling System

SCP-W Series Semi Automatic Pneumatic Impulse Sealer is sealing machine equipped with pneumatic cylinder. SCP-W Series with built in water cooling system for Mass Production. Machine design with bottom jaw sealing is suitable for sealing various plastic film bags with sealing length of 600mm and 10mm sealing width.

SCP-W Series design adopts with pneumatic cylinder required compressed air as motive power with adjustable sealing pressure and separate programmable timers for heating, congealing and recycling for different material thickness. Once correct setting have been programmed, consistent seals and cooling are maintained automatically for perfect sealing quality.

** Customized specification available upon request.

TECHNICAL DATA

Model	KST-SCP600W
Sealing Length	600mm
Sealing Width	10mm
Sealing Thickness	2 X 0.15 / 0.4 mm
Sealing Jaw	Bottom Only
Sealing Jaw Operation	Pneumatic Cylinder
Heat Time	0 - 2 sec
Cooling Time	0 - 10 sec
Voltage	1 Phase 240V
Sealing Power	1500 W
Cooling System	Water
Air Compressor (prepare by customer)	0.4 - 0.6 Mpa
Machine Structure	Paint
Machine Weight	30kg
Machine Dimension	1100mmL x 550mmD x 850mmH

