



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



Induction Sealing Machine

Induction Sealing Machine also known as Aluminium Foil Sealing Machine is the perfect machine to hermetically seal with aluminium foil all types of products (except metal bottles) to prevent leakage, contamination, and mildew formation, and to extend the shelf-life of any kind of product. The induction sealer transmits electromagnetic energy which is received by the aluminium foil liner causing it to heat up and weld itself across the container neck. Works on various types of plastic laminated (composite) aluminium foils such as PE, PP, PET & PVC.

Induction Sealer widely used as sealing package machine in industries such as pharmaceuticals, food, pesticides, lubricants and cosmetics etc. Induction sealing applies to liquid products like beverages and automotive oil, and dried products like pharmaceuticals medicine, food powders and dry grain products in container.

SF1300A Table Top Continuous Induction Sealer

SF1300A Series Table Top Continuous Induction Sealer utilizes electro magnetic induction principle to produce instant high heat to melt aluminium foil to seal bottles. SF1300A complete with table top conveyor may increase the production speed and reduce labour.

SF1300A Table Top Continuous Induction Sealer is special for container with sealing diameter range between 15mm - 60mm. SF1300A complete with table top conveyor may increase the production speed and reduce labour.

Optional : a. Adjustable Height range increase to 40mmH - 300mmH



TECHNICAL DATA

MODEL	SF1300A		
Voltage	1 Phase 240V	Conveyor Speed	0 - 12.5 mtr/min
Max. Power	1300 W	Sealing Speed	0 - 80 bottles/min
Sealing Diameter	15mm - 60mm	Cooling Method	Fan Air Cooling
Operate Model	table top with conveyor	Machine Structure	Stainless Steel
Conveyor Dimension	135mmW x 780mmL	Machine Weight	34 Kg
Adjustable Height from Conveyor to Sealing Head	20mmH - 180mmH	Main Machine Dimension	805mmL x 395mmW x 330mmH